

# H2 5-10K Three Phase Hybrid Inverter

SAJ's hybrid inverter supported easy setting of smart working modes, UPS 10ms switch time and fast charging/discharging speed of battery. H2 covers 5-10kW, 2MPPTs and three phase grid.



- ❑ Easy setting of smart working modes
- ❑ AFCI (optional)
- ❑ DC 15A string matched with ultra high PV modules
- ❑ Battery fast charging/ discharging supported
- ❑ Supported 100% three phase voltage imbalance
- ❑ With UPS function switch time  $\leq 10\text{ms}$
- ❑ 110% AC overloading

H2-5K-T2 | H2-6K-T2  
H2-8K-T2 | H2-10K-T2

MODEL	H2-5K-T2	H2-6K-T2	H2-8K-T2	H2-10K-T2
<b>DC Input</b>				
Max. PV Array Power [Wp]@STC	7500	9000	12000	15000
Max. DC Voltage [V]			1000	
MPPT Voltage Range [V]			180~900	
Rated DC Voltage [V]			600	
Start Voltage [V]			180	
Max. DC Input Current [A]			15 / 15	
Max. DC Short Circuit Current [A]			19/19	
No. of MPPT			2	
<b>Battery Parameters</b>				
Battery Type			LiFePO4	
Battery Voltage Range [V]			180~600	
Max. Charging/Discharging Current [A]			30/30	
<b>AC Output [On-grid]</b>				
Rated AC Power [W]	5000	6000	8000	10000
Rated Apparent Power [VA]	5000	6000	8000	10000
Max. Apparent Power [VA]	5500	6600	8800	11000
Rated Output Current [A]@230Vac	7.2	8.7	11.6	14.5
Max. Output Current [A]	8	9.6	12.8	15.9
Current Inrush [A]			52.0	
Max. AC Fault Current [A]			45.0	
Max. AC Over Current Protection [A]	20.8	25.0	33.3	41.8
Rated AC Voltage/Range [V]		3L+N+PE, 220/380, 230/400, 240/415; 180 ~ 280/312 ~ 485		
Rated Output Frequency/Range [Hz]		50,60/45 ~ 55,55 ~ 65		
Power Factor [cos φ]		0.8 leading ~ 0.8 lagging		
Total Harmonic Distortion [THDi]		<3%		
<b>AC Input [On-grid]</b>				
Rated AC Voltage/Range [V]		3L+N+PE, 220/380, 230/400, 240/415; 180 ~ 280/312 ~ 485		
Rated Input Frequency [Hz]		50,60		
Max. Input Current [A]@230Vac	14.5	17.4	23.2	29
<b>AC Output [Back-up]</b>				
Max. Output Power [VA]	5000	6000	8000	10000
Max. Output Current [A]	7.2	8.7	11.6	14.5
Peak Output Apparent Power [VA]	10000, 60s	12000, 60s	16000, 60s	16500, 60s
Rated AC Voltage/Range [V]		3L+N+PE, 220/380, 230/400, 240/415; 180 ~ 280/312 ~ 485		
Rated Output Frequency/Range [Hz]		50,60/45 ~ 55,55 ~ 65		
Output THDv (@ Linear Load)		<3%		
<b>Efficiency</b>				
Max. Efficiency			98.0%	
Euro Efficiency			97.6%	
<b>Protection</b>				
Battery Input Reverse Polarity Protection			Integrated	
Over load Protection			Integrated	
AC Short Circuit Current Protection			Integrated	
DC Surge Protection			Integrated	
AC Surge Protection			Integrated	
Anti-islanding Protection			Integrated (AFD)	
AFCI Protection			Optional	
RSD Protection			Optional	
<b>Interface</b>				
PV Connection			MC4/D4	
AC Connection			Plug-in connector	
Battery Connection			Quick connector	
Display			LED+APP	
Communication			Wifi/ethernet/4G (optional)	
<b>General Parameters</b>				
Topology			Non-isolated	
Operating Temperature Range		-25°C to +60°C (45°C to 60°C with derating)		
Cooling Method		Natural convection		
Ambient Humidity		0~100% Non-condensing		
Altitude		3000m (>2000m power derating)		
Noise [dBA]		<30		
Ingress Protection		IP65		
Protection Class		I		
Dimensions [H*W*D] [mm]		433*549*207		
Weight [kg]		25		
Warranty [Year]		Refer to the warranty policy		
Standard		EN 62109-1/2, EN 61000-6-2/4, EN 50438, EN 50549, C10/11, IEC 62116, IEC 61727, RD 1699, RD 413, UNE 206006, UNE 206007, NTS, CEI 0-16, CEI 0-21, AS 4777.2, NBR 16149, NBR 16150, VDE-AR-N 4105, VDE 0126-1-1		

Manufacturer: Guangzhou Sanjing Electric Co., Ltd.  
Made in China

Products are continuously updated and parameters are just for references.

V1.2-20260303